

GREIF CONTAINERS, INC.
BRADLEY PLANT
DOT REGISTRATION NUMBER -" GBC"

IBC CLOSING STATEMENT
CFR 49 PART 178
178.2(c) (1) NOTIFICATION

All plastic containers should be closed after filling and before transportation in accordance with the closing specifications stated below.

TORQUE SPECIFICATIONS FOR VALVES

<i>Valve</i>	<i>GASKETS</i>	VALVE TIGHTENING TORQUE
IPCC: Ball Valve or Cylinder Valve	Viton, EPDM	50 ft. lbs.

TORQUE SPECIFICATIONS FOR 2" PLUG/GASKET COMBINATIONS

		<i>PLUG TIGHTENING TORQUE</i>	
PLUG TYPE	<i>GASKETS</i>	2" Dia. NPS	2" Dia. Buttress
IPCC: Copolymer Polypropylene	Santoprene	20 ft. lbs.	20 ft. lbs.

TORQUE SPECIFICATIONS FOR 6" CAP

CAP TYPE	<i>GASKETS</i>	CAP TIGHTENING TORQUE
IPCC: Copolymer Polypropylene	Santoprene	45 ft. lbs.

Units Of Measure

Ft. lbs. = Torque in foot pounds

FRM-IBCCLOSE Revision # 0 Issue Date: 12/01/10